



AUGERTORQUE
EARTHMOVING ATTACHMENTS



CANGINI

MULCHER



IDEAL FOR FOREST CARE, PARKS AND GARDEN MAINTENANCE

Heavy operations such as bushwood clearance or land maintenance are perfect applications for the Cangini Mulcher/flail.

This attachment is rugged and durable, thanks above all to its reinforced casing with double bottom, which provides outstanding resistance to impacts and torsional forces. The shielded bearings of the rollers protect them from collisions with material in the mulching area. Use this renowned attachment on excavators from 1.5T to 6.5T.

Reinforced body

Double reinforced body for higher resistance to shocks

Shaft with Hammers

Suitable for cutting shrubs or similar plants

Shaft with Blades

Suitable for cutting grass or similar vegetation



Integrated Valve Unit

Throttle, pressure relief and bypass valves

Gear Motor

Motor with reinforced seals in case of back pressure higher than 10 bar

Coupling Adjustment Slide

The coupling position can be differently adjusted.

www.augertorque.com

CALL 01451 861652

EMAIL sales@augertorque.com

OR CONTACT YOUR NEAREST DEALER

Features

- ▶ Shaft equipped with either blade or hammer set up
- ▶ Adjustable height support roller
- ▶ High quality motor and hoses
- ▶ Self levelling frontal plane
- ▶ Highly resistant with an integrated valve unit as standard

Applications

- ▶ Ground clearance
- ▶ Woodland pathway creation and maintenance
- ▶ Clear and maintain vegetation
- ▶ Tree and hedge trimming
- ▶ Mulch trees and hedges down to ground level
- ▶ Cut shrubs up to 10cm in diameter

Specifications

Models		TC0-70	TC1-60	TC1-80	TC2-80	TC2-100
Carrier weight		1.5T	1.5 - 3.5T	1.5 - 3.5T	3.5 - 6.5T	3.5 - 6.5T
Drum width	mm (inch)	700 (28)	600 (24)	800 (31)	800 (31)	1000 (39)
Overall width	mm (inch)	915 (36)	800 (31)	1000 (39)	980 (39)	1180 (46)
Depth	mm (inch)	516 (20)	640 (25)	640 (25)	810 (32)	810 (32)
Height	mm (inch)	417 (17)	461 (18)	461 (18)	530 (21)	530 (21)
Weight	kg (lbs)	83 (183)	100 (220)	115 (254)	245 (540)	270 (595)
Flow rate	lpm (gpm)	14 - * (3.6 - *)	18 - 90 (5 - 24)	18 - 90 (5 - 24)	28 - 90 (7 - 24)	28 - 90 (7 - 24)
Pressure	bar (psi)	250 (3626)	250 (3626)	250 (3626)	250 (3626)	250 (3626)
Cutting diameter with hammer	mm (inch)	15 - 20 (0.6 - 0.8)	20 - 30 (0.8 - 1.2)	20 - 30 (0.8 - 1.2)	40 - 60 (1.6 - 2.4)	40 - 60 (1.6 - 2.4)



Part of the Auger Torque landscaping range

STUMP PLANERS | LOG SPLITTERS | MULCHERS | HEDGE TRIMMERS | SWEEPER BROOMS